

PC 667

Specialty/Outdoor UV Exposure  
Cloth Duct Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Excellent protective masking of various materials such as steel, vinyl, aluminum and anodized metals

### ADVANTAGES AND BENEFITS

- > Excellent UV resistance
- > Clean removal, no residue after 14 days exposure
- > Easy tear
- > Waterproof backing
- > High tack

### CONSTRUCTION

**Overall Grade/Function:** Specialty/Outdoor UV exposure

**Backing:** Waterproof, UV resistant polyethylene film with a polyester cloth carrier

**Adhesive:** Combination synthetic/natural rubber

### COLOR(S)



Red (RED)



### STANDARD WIDTH(S)

48 mm    72 mm

### STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	22 lbs/in width	37.92 N/10 mm
Adhesion to Stainless Steel	50 oz/in width	5.38 N/10 mm
Thickness	9 mils	0.228 mm
Elongation	15 %	15 %
Maximum Temperature	200 F	93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.