

TECHNICAL DATA

TYPICAL APPLICATIONS

- > HVAC applications
- > Sealing, seaming and holding sheet metal duct work
- > Holding, bundling, splicing, seaming, sealing, protective packaging

ADVANTAGES AND BENEFITS

- > Co-extrusion construction – delamination free
- > Excellent unwind and tearability characteristics
- > Excellent holding power
- > Waterproof backing

CONSTRUCTION

Overall Grade/Function: Contractor Grade

Backing: Waterproof, polyethylene film with a polyester/cotton blend cloth carrier

Adhesive: Natural rubber

COLOR(S)



Black (BLK)



Silver (SIL)

STANDARD WIDTH(S)

48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.



PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	32 lbs/in width	56.0 N/10 mm
Adhesion to Stainless Steel	60 oz/in width	6.57 N/10 mm
Thickness	11.5 mils	0.29 mm
Elongation	10 %	10 %
Service Temperature Range	50 F to 200 F	10 C to 93 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

APPLICABLE SPECIFICATIONS

Tested in accordance with UL 723 – Flame Spread Index 5, Smoke Development Index 5

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.