

## TECHNICAL DATA

## TYPICAL APPLICATIONS

- > Masking of both primed and painted sheetrock
- > Designed for use on wallboard, woodwork, ceramic tile and knockdowns.

## ADVANTAGES AND BENEFITS

- > Provides easy unwind with excellent conformability
- > Specially formulated adhesive provides clean removal leaving no residue
- > Fine structured crepe backing offers superior paint lines
- > Abrasion and moisture resistant
- > Excellent adhesion to most surfaces
- > Resist curling
- > Excellent for rounding curves and contours

## CONSTRUCTION

Overall Grade/Function: Premium Grade

Backing: Fine Structured Crepe Paper

Adhesive: Moderate Tack, Rubber based adhesive



## COLOR(S)



Natural (NAT)

## STANDARD WIDTH(S)

24mm      36mm      48mm

## STANDARD LENGTH(S)

55m

Contact your Shurtape sales representative for other available sizes.

## PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	39.64 N/10 mm
Adhesion to Stainless Steel	34 oz/in width	3.7 N/10 mm
Thickness	7.1 mils	.18 mm
Elongation	10 %	10 %
Service Temperature Range	45 F to 100 F	7 C to 38 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

## APPLICABLE SPECIFICATIONS

ASTM D6123/D6123M-97

## STORAGE &amp; USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.