

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Outstanding tape for a wide range of industrial applications – available in five vibrant colors
- > Printable – the perfect tape for identification labeling and ideal or combination consumer packaging
- > Widely used for bag sealing, color coding and packaging closures

ADVANTAGES AND BENEFITS

- > High strength rope paper tape that is directly printable with water and solvent based flexo-graphic inks
- > Recommended for printed legends
- > Easy unwind and high tear resistance
- > Excellent adhesive-to-adhesive holding power
- > Highest possible adhesion consistent with printability
- > Totally opaque backing masks any color over which the tape is placed – including black

CONSTRUCTION

Overall Grade/Function: Ultimate Premium Grade

Backing: High strength impregnated rope paper

Adhesive: Synthetic rubber

COLOR(S)



STANDARD WIDTH(S)

24 mm 48 mm

STANDARD LENGTH(S)

55 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	50 lbs/in width	87.6 N/10mm
Adhesion to Stainless Steel	65 oz/in width	7.11 N/10mm
Thickness	6.0 mils	0.15 mm
Elongation	3 %	3 %
Maximum Service Temperature	150 F	66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.