

DF 63

General Purpose, Double-Faced  
Crepe Paper Tape

Shurtape®

## TECHNICAL DATA

### TYPICAL APPLICATIONS

- > Mounting, holding, splicing, tabbing and fastening of a variety of substrates

### ADVANTAGES AND BENEFITS

- > Durability
- > Good tensile strength
- > Superior adhesion to a variety of substrates
- > Both tape and release liner are wrinkle-resistant

### CONSTRUCTION

Overall Grade/Function: General Purpose

Backing: Crepe paper

Adhesive: Smooth, rubber based adhesive

Liner: Non-contaminating, siliconized, crepe paper  
release liner

### COLOR(S)



White (WHI)



### STANDARD WIDTH(S)

18 mm    24 mm

### STANDARD LENGTH(S)

33 m

Contact your Shurtape sales representative for other available sizes.

### PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	23 lbs/in width	40.3 N/10 mm
Adhesion to Stainless Steel	29 oz/in width	3.17 N/10 mm
Thickness	6.4 mils	0.16 mm
Elongation	9 %	9 %
Service Temperature Range	50 F to 225 F	10 C to 107 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

### APPLICABLE SPECIFICATIONS

A-180B Type II Grade A

### STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.