

PP 808

UPVC General Purpose
Bag Sealing Tape

Shurtape®

TECHNICAL DATA

TYPICAL APPLICATIONS

- > Sealing bags – may be used with Shurtape dispenser SD 937
- > Light weight sealing, banding, bundling, packaging
- > Color coding

ADVANTAGES AND BENEFITS

- > Will hold in sub-freezing temperatures
- > Moisture proof

CONSTRUCTION

Overall Grade/Function: General Purpose, bag sealing

Backing: Unplasticized polyvinylchloride film (UPVC)

Adhesive: High tack, natural rubber



COLOR(S)



Red (RED)



Green (GRN)

STANDARD WIDTH(S)

9 mm

STANDARD LENGTH(S)

165 m

Contact your Shurtape sales representative for other available sizes.

PHYSICAL PROPERTIES

	STANDARD	METRIC
Tensile Strength	27 lbs/in width	47.3 N/10 mm
Adhesion to Stainless Steel	24 oz/in width	2.63 N/10 mm
Thickness	2.1 mils	0.05 mm
Elongation	60 %	60 %
Application Temperature Range	20 F to 110 F	-7 C to 43 C
Service Temperature Range	0 F to 150 F	-18 C to 66 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC. Quality Assurance and Technical Service Departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.

STORAGE & USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.